

## Specs & Compare

Compare Kubota Engines



### V2403-CR-TI-E4-BG

30.6 kW / 41.0 HP / 1800 RPM

#### Specifications

Emission Regulations	EPA/CARB Tier 4
Type	Vertical, water cooled 4-cycle diesel engine
Cylinders	4
Bore and Stroke in (mm)	3.43 × 4.031 (87.0 x 102.4)
Displacement cu. in. (L)	148.5 (2.434)
Aspiration	Turbocharged + Turbo After Cooler
After treatment	DOC
Stand-by output/speed* kW (HP) / rpm	45.1 (33.6)/ 1800
Continuous output/speed* kW (HP) / rpm	41.0 (30.6)/ 1800

<b>Combustion System</b>	Direct injection
<b>Fuel System</b>	Common rail system
<b>Length × Width × Height** (without after treatment unit)</b> in (mm)	26.3 × 21.6 × 28.7 (669 × 549 × 728)
<b>Length × Width × Height*** (with after treatment unit)</b> in (mm)	33.1 × 21.6 × 29.3 (842 × 549 × 745)
<b>Dry Weight</b> lb (kg)	551 (250)

Specifications are subject to change without notice.

DOC: Diesel Oxidation Catalyst

Dimensions and dry weight are according to Kubota's standard specification.

Dimensions and weight depend on completed specifications.

\*1: SAE J1349 net stand-by

\*2: SAE J1349 net continuous

\*3: Exclude cooling fan and exclude aftertreatment unit

\*4: Exclude cooling fan and include aftertreatment unit on engine