

Specs & Compare

Compare Kubota Engines



V2203-M-E3-BG

20.2 kW / 27.1 HP / 1800 RPM

Specifications

| | |
|---|--|
| Emission Regulations | EPA/CARB interim Tier 4 level |
| Type | Vertical, water cooled 4-cycle diesel engine |
| Cylinders | 4 |
| Bore and Stroke in (mm) | 3.43 × 3.64 (87.0 x 92.4) |
| Displacement cu. in. (L) | 134.1 (2.197) |
| Aspiration | Naturally Aspirated |
| After treatment | - |
| Stand-by output/speed* kW (HP) / rpm | 32.5 (24.2)/ 1800 |
| Continuous output/speed* kW (HP) / rpm | 27.1 (20.2)/ 1800 |

| | |
|---|--------------------------------------|
| Combustion System | Indirect Injection |
| Fuel System | In-line pump |
| Length × Width × Height** (without after treatment unit) in (mm) | 26.3 × 18.9 × 24.9 (669 × 481 × 633) |
| Length × Width × Height*** (with after treatment unit) in (mm) | - |
| Dry Weight lb (kg) | 441 (200) |

Specifications are subject to change without notice.

Dimensions and dry weight are according to Kubota's standard specification.

Dimensions and weight depend on completed specifications.

*1: SAE J1349 net stand-by

*2: SAE J1349 net continuous

*3: Exclude cooling fan and exclude aftertreatment unit

*4: Exclude cooling fan and include aftertreatment unit on engine