

## Specs & Compare

Compare Kubota Engines



### V1505-E3-BG

13.4 kW / 18.0 HP / 1800 RPM

#### Specifications

Emission Regulations	EPA/CARB Tier 4 level
Type	Vertical, water cooled 4-cycle diesel engine
Cylinders	4
Bore and Stroke in (mm)	3.07 × 3.09 (78.0 x 78.4)
Displacement cu. in. (L)	91.41 (1.498)
Aspiration	Naturally aspirated
After treatment	-
Stand-by output/speed* kW (HP) / rpm	20.2 (15.1)/ 1800
Continuous output/speed* kW (HP) / rpm	18.0 (13.4)/ 1800

<b>Combustion System</b>	Indirect injection
<b>Fuel System</b>	In-line pump
<b>Length × Width × Height**</b> (without after treatment unit) in (mm)	23.7 × 15.4 × 23.9 (601 × 391 × 607)
<b>Length × Width × Height***</b> (with after treatment unit) in (mm)	-
<b>Dry Weight</b> lb (kg)	280 (127)

Specifications are subject to change without notice.

Dimensions and dry weight are according to Kubota's standard specification.

Dimensions and weight depend on completed specifications.

\*1: SAE J1349 net stand-by

\*2: SAE J1349 net continuous

\*3: Exclude cooling fan and exclude aftertreatment unit

\*4: Exclude cooling fan and include aftertreatment unit on engine