


LIQUID COOLED NAT. GAS ENGINE GENERATOR SET

60 HZ MODEL
SP-5000

Model	STANDBY 120°C RISE		
	HZ	LPG	N.G.
SP-5000-60 HERTZ	60	300	500



All generator sets are USA prototype built and thoroughly tested. Production models are USA factory built and 100% load tested.



“OPEN” GEN-SET

There is no enclosure, so gen-set must be placed within a weather protected area, un-inhabited by humans or animals, with proper ventilation. Silencer not supplied, as installation requirements are not known. However, this item is available as optional equipment.



UL2200, UL1446, UL508, UL142, UL498



NFPA 110, 99, 70, 37

All generator sets meet NFPA-110 Level 1, when equipped with the necessary accessories and installed per NFPA standards.



NEC 700, 701, 702, 708



NEMA ICS10, MG1, ICS6, AB1




ANSI C62.41, 27, 59, 32, 480, 40Q, 81U, 360-05



ASCE 7-22

All generator sets meet 200 MPH rating.



“LEVEL 2” HOUSED GEN-SET

Full aluminum weather protection and superior sound attenuation for specific low noise applications. Critical grade muffler is standard.



EPA 40CFR Part 60, 1048, 1054, 1065, 1068

GENERATOR RATINGS

GENERATOR MODEL	VOLTAGE		PH	HZ	LIQUID PROPANE GAS FUEL		NATURAL GAS FUEL	
	L-N	L-L			120°C RISE STANDBY RATING		120°C RISE STANDBY RATING	
					KW/KVA	AMP	KW/KVA	AMP
SP-5000-3-2	120	208	3	60	300/400	1042	500/625	1736
SP-5000-3-3	120	240	3	60	300/400	903	500/625	1505
SP-5000-3-4	277	480	3	60	300/400	451	500/625	752
SP-5000-3-5	127	220	3	60	300/400	985	500/625	1642
SP-5000-3-16	346	600	3	60	300/400	361	500/625	602

RATINGS: All three phase gen-sets are 12 lead windings, rated at .8 power factor. 120°C “STANDBY RATINGS” are strictly for gen-sets that are used for back-up emergency power to a failed normal utility power source. This standby rating allows varying loads, with no overload capability, for the entire duration of utility power outage. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based on 120°C (standby) R/R winding temperature, within a maximum 40°C ambient condition. Generators operated at standby power ratings must not exceed the temperature rise limitation for class H insulation system, as specified in NEMA MG1-22.40. Specifications & ratings are subject to change without prior notice.

APPLICATION AND ENGINEERING DATA FOR MODEL SP-5000-60 HZ

GENERATOR SPECIFICATIONS

Manufacturer..... Stamford Electric Generators
 Model & Type..... HCI534E-311, 4 Pole, 12 Lead, Three Phase
 HCI534D-311, 4 Pole, 12 Lead, 480V, Three Phase
 HCI534D-17, 4 Pole, 6 Lead, 600V, Three Phase
 Exciter..... Brushless, shunt excited
 Voltage Regulator..... Solid State, HZ/Volts
 Voltage Regulation ½%, No load to full load
 Frequency Field convertible, 60 HZ to 50 HZ
 Frequency Regulation..... ½% (½ cycle, no load to full load)
 Unbalanced Load Capability 100% of standby amps
 Total Stator and Load Insulation Class H, 180°C
 Temperature Rise..... 120°C R/R, standby rating @ 40°C amb.
 3 Ø Motor Starting @ 30% Voltage Dip (208-240V) .. 1340 kVA
 3 Ø Motor Starting @ 30% Voltage Dip (480V)..... 1750 kVA
 3 Ø Motor Starting @ 30% Voltage Dip (600V)..... 1520 kVA
 Bearing..... 1, Pre-lubed and sealed
 Coupling Direct flexible disc
 Total Harmonic Distortion..... Max 3 | % (MIL-STD705B)
 Telephone Interference Factor..... Max 50 (NEMA MG1-22)
 Deviation Factor Max 5% (MIL-STD 405B)
 Ltd. Warranty Period 24 Months from date of start-up or
 1000 hours use, first to occur.

GENERATOR FEATURES

- World Renown Stamford Electric Generator having UL-1446 certification on full amortisseur windings.
- Full generator protection with **Deep Sea 7420** controller, having UL-508 certification.
- Automatic voltage regulator with over-excitation, under-frequency compensation, under-speed protection, and EMI filtering. Entire solid-state board is encapsulated for moisture protection.
- Generator power ratings are based on temperature rise, measured by resistance method, as defined in MIL-STD 705C and IEEE STD 115, Method 6.4.4.
- Power ratings will not exceed temperature rise limitation for class H insulation as per NEMA MG1-22.40.
- Insulation resistance to ground, exceeds 1.5 meg-ohm.
- Stator receives 2000 V. hi-potential test on main windings, and rotor windings receive a 1500 V. hi-potential test, as per MIL-STD 705B.
- Complete engine-generator torsional acceptance, confirmed during initial prototype testing.
- Full load testing on all engine-generator sets, before shipping.
- Self ventilating and drip-proof & revolving field design

ENGINE SPECIFICATIONS AND APPLICATIONS DATA

ENGINE

Manufacturer..... Power Solutions Inc. (PSI)
 Model and Type..... Heavy Duty, 21.9LTCAC HO, 4 cycle
 Aspiration Turbocharged & Charge Air Cooled
 Cylinder Arrangement 12 Cylinders, Vee
 Displacement Cu. In. (Liters) 1336 (21.9)
 Bore & Stroke In. (Cm.) 5.0 x 5.6 (128 x 142)
 Compression Ratio..... 10.5:1
 Main Bearings & Style 14, Precision Half-Shell
 Cylinder Head..... Cast Iron
 Pistons..... Cast Aluminum
 Crankshaft..... Forged Steel
 Exhaust Valve..... Inconel, A193
 Governor Electronic
 Frequency Reg. (no load-full load)..... Isochronous
 Frequency Reg. (steady state)..... ± 1/4%
 Air Cleaner..... Dry, Replaceable Cartridge
 Engine Speed 1800
 Piston Speed, ft/min (m./min)..... 1677 (510)
 Max Power, bhp (kwm) Standby/LPG 472 (352)
 Max Power, bhp (kwm) Standby/NG 764 (570)
 Ltd. Warranty Period 12 Months or 2000 hrs., first to occur

FUEL SYSTEM

Type LPG or NAT. GAS, Vapor Withdrawal
 Fuel Pressure (kpa), in. H₂O* (2.74 -3.48), 11"-14"
 Secondary Fuel Regulator..... NG or LPG Vapor System
 Auto Fuel Lock-Off Solenoid..... Standard on all sets
 Fuel Supply Inlet Line (2) 2" NPTF

FUEL CONSUMPTION

LP GAS: FT ³ /HR (M ³ /HR)	STANDBY
100% LOAD	1601 (45.3)
75% LOAD	1201 (34.0)
50% LOAD	809 (22.9)
LPG = 2500 BTU X FT³/HR = Total BTU/HR	
LPG Conversion: 8.50 FT³ = 1 LB. : 36.4 FT³ = 1 GAL.	

NAT. GAS: FT ³ /HR (M ³ /HR)	STANDBY
100% LOAD	5346 (151)
75% LOAD	4350 (123.2)
50% LOAD	3300 (93.4)
NG = 1000 BTU X FT³/HR = Total BTU/HR	

OIL SYSTEM

Type Full Pressure
 Oil Pan Capacity qt. (L) 42.3 (40.0)
 Oil Pan Cap. W/ filter qt. (L) 49.1 (47.1)
 Oil Filter 2, Replaceable Spin-On

ELECTRICAL SYSTEM

Ignition System Electronic
 Eng. Alternator/Starter: 24 VDC, negative ground, 45 amp/hr.
 Recommended battery to -18°C (0° F): ... (2) 12 VDC, BCI# 31,
 Max. Dimensions: 14"lg x 6 3/4" wi x 10" hi, with standard
 round posts. Min output 1000 CCA. Battery tray (max. dim. at
 15"lg x 7"wi). This model has (2) battery trays, (2) hold down
 straps, (2) sets of battery cables, and (1) battery charger.
 Installation of (2) 12VDC starting batteries connected in series
 for 24VDC output is required, with possible higher AMP/HR
 rating, as described above, if the normal environment
 temperature averages -13° F (-25°C) or cooler.

APPLICATION AND ENGINEERING DATA FOR MODEL SP-5000-60 HZ

COOLING SYSTEM

Type of System.....Pressurized, closed recovery
 Coolant Pump Pre-lubricated, self-sealing
 Cooling Fan Type (no. of blades).....Pusher (8)
 Fan Diameter inches (mm) 52" (1321)
 Ambient Capacity of Radiator °F (°C).....125 (51.6)
 Engine Jacket Coolant Capacity Gal (L)14 (53.0)
 Radiator Coolant Capacity Gal. (L).....50 (189)
 Maximum Restriction of Cooling Air Intake
 and discharge side of radiator in. H₂O (kpa) 0.5 (.125)
 Water Pump Capacity gpm (L/min)174 (660)
 Heat Reject Coolant: Btu/min (kw).....25,760 (453)
 Low Radiator Coolant Level Shutdown.....Standard
 Note: Coolant temp. shut-down switch setting at 230°F (110°C) with 50/50
 (water/antifreeze) mix.

AIR REQUIREMENTS

Combustion Air, cfm (m³/min)1027 (29.1)
 Radiator Air Flow cfm (m³/min)39,995 (1133)
 Heat Rejected to Ambient:
 Engine: kw (btu/min).....66 (3765)
 Alternator: kw (btu/min)27 (1580)

EXHAUST SYSTEM

Exhaust Outlet Size (2) 5"
 Max. Back Pressure, in. hg (KPA)3.0 (10.2)
 Exhaust Flow, at rated kw: cfm (m³/min).....3179 (89.8)
 Exhaust Temp., at rated kw: °F (°C)1382 (750)
 Engines are EPA certified for Natural Gas.

SOUND LEVELS MEASURED IN dB(A)

	<u>Open Set</u>	<u>Level 2 Encl.</u>
Level 2, Critical Silencer	97	82
Level 3, Hospital Silencer.....		76

Note: Open sets (no enclosure) has (2) optional silencer system choices due to unknown job-site applications. Level 2 enclosure has installed critical silencer with upgrade to hospital silencer. Sound tests are averaged from several test points and taken at 23 ft. (7 m) from source of noise at normal operation.

DERATE GENERATOR FOR ALTITUDE

3% per 1000 ft.(305m) above 3000 ft. (914m) from sea level

DERATE GENERATOR FOR TEMPERATURE

2% per 10°F(5.6°C) above 104°F (40°C)

DIMENSIONS AND WEIGHTS

	<u>Open Set</u>	<u>Level 2 Enclosure</u>
Length in (cm)	168 (427)	216 (548)
Width in (cm).....	82 (208)	82 (208)
Height in (cm).....	92 (234)	100 (254)
3 Ø Net Weight lbs (kg).....	10225 (4638)	12725 (5772)
3 Ø Ship Weight lbs (kg).....	10625 (4820)	13125 (5954)

DEEP SEA 7420 DIGITAL MICROPROCESSOR CONTROLLER



DEEP SEA 7420

The 7420 controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which continuously displays the status of the engine and generator at all times.

The 7420 controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs • (8) configurable outputs • voltage monitoring • mains (utility) failure detection.

- (250) event logs
 - configurable timers
 - automatic shutdown or warning during fault detection
 - remote start (on load)
 - engine preheat
 - advanced metering capability
 - hour meter
 - text LCD displays
 - protected solid state outputs
 - test buttons for: stop/reset
 - manual mode
 - auto mode
 - lamp test
 - start button
 - power monitoring (kWh, kVar, kVAh, kVArh)
- This controller includes expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSENet for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.

LOW LOAD CONDITIONS: Operation of PSI HD engines at low-load conditions should be limited to no more than one (1) hour per twenty-four (24) hour period. If the application requires extended time at light loads, it is recommended that the engine load be increased to at least 70% of mechanical rating for a minimum of two (2) hours per fifty (50) hours of low-load operation. Piston sealing rings rely on adequate cylinder firing pressure and temperature to seal the combustion chamber and prevent excessive engine oil from entering the power cylinder. Under low loads these rings will not seal properly, resulting in oil being burned in the combustion chamber and carbon deposits on pistons and valves. This mechanism is well-documented in reciprocating engines of all fuel types and is often referred to as "wet-stacking."

STANDARD FEATURES FOR MODEL SP-5000-60 HZ

STANDARD FEATURES

CONTROL PANEL:

- Deep Sea 7420 digital microprocessor with logic allows programming in the field. Controller has:
- STOP-MANUAL-AUTO modes and automatic engine shutdowns, signaled by full text LCD indicators:
 - Low oil pressure • Engine fail to start
 - High engine temp • Engine over speed
 - Low Radiator Level • Engine under speed
 - Three auxiliary alarms • Over & under voltage
 - Battery fail alarm
- Also included is tamper-proof engine hour meter

ENGINE:

- Full flow oil filter • Air filter • Oil pump • Solenoid type starter motor • Hi-temp radiator • Jacket water pump
- Thermostat • Pusher fan and guard • Exhaust manifold
 - 24 VDC battery charging alternator • Flexible exhaust connector • "Isochronous" duty, electronic governor • Secondary dry fuel regulator • Dry fuel lock-off solenoid • Vibration isolators • Closed coolant recovery system with 50/50 water to anti-freeze mixture • flexible oil & radiator drain hose.

AC GENERATOR SYSTEM:

- AC generator • Shunt excited • Brushless design • Circuit Breaker installed and wired to gen-set • Direct connection to engine with flex disc • Class H, 180°C insulation • Self ventilated • Drip proof construction • UL Certified

VOLTAGE REGULATOR:

- ½% Voltage regulation • EMI filter • Under-speed protection • Over-excitation protection • total encapsulation

DC ELECTRICAL SYSTEM:

- Battery tray • Battery cables • Battery hold down straps
- 2-stage battery float charger with maintaining & recharging automatic charge stages

WEATHER/SOUND PROOF ALUMINUM HOUSING CORROSION RESISTANT PROTECTION CONSISTING OF:

- 9 Heated and Agitated Wash Stages
- Zinc Phosphate Etching-coating Stage
- Final Baked On Enamel Powder Coat
- 18/8 Stainless Steel Hardware

Design & specifications subject to change without prior notice. Dimensions shown are approximate. Contact for certified drawings. DO NOT USE DIMENSIONS FOR INSTALLATION PURPOSES.

