


Specs & Compare

Compare Kubota Engines



V3600-T-E3-BG

39.2 kW / 52.6 HP / 1800 RPM

Specifications

Emission Regulations	EPA/CARB interim Tier 4 level
Type	Vertical, water cooled 4-cycle diesel engine
Cylinders	4
Bore and Stroke in (mm)	3.86 × 4.724 (98.0 x 120.0)
Displacement cu. in. (L)	220.9 (3.620)
Aspiration	Turbocharged
After treatment	-
Stand-by output/speed* kW (HP) / rpm	57.8 (43.1)/ 1800
Continuous output/speed* kW (HP) / rpm	52.6 (39.2)/ 1800

Combustion System	Indirect injection
Fuel System	In-line pump
Length × Width × Height** (without after treatment unit) in (mm)	29.1 × 21.1 × 31.5 (738 × 537 × 800)
Length × Width × Height*** (with after treatment unit) in (mm)	-
Dry Weight lb (kg)	626 (284)

Specifications are subject to change without notice.

Dimensions and dry weight are according to Kubota's standard specification.

Dimensions and weight depend on completed specifications.

*1: SAE J1349 net stand-by

*2: SAE J1349 net continuous

*3: Exclude cooling fan and exclude aftertreatment unit

*4: Exclude cooling fan and include aftertreatment unit on engine