


## Specs & Compare

Compare Kubota Engines



### V3800DI-T-E3-BG

47.5 kW / 63.7 HP / 1800 RPM

#### Specifications

Emission Regulations	EPA/CARB Tier 3 level
Type	Vertical, water cooled 4-cycle diesel engine
Cylinders	4
Bore and Stroke in (mm)	3.937 × 4.724 (100.0 x 120.0)
Displacement cu. in. (L)	230.0 (3.769)
Aspiration	Turbocharged
After treatment	-
Stand-by output/speed* kW (HP) / rpm	70.1 (52.3)/ 1800
Continuous output/speed* kW (HP) / rpm	63.7 (47.5)/ 1800

<b>Combustion System</b>	Direct injection
<b>Fuel System</b>	In-line pump
<b>Length × Width × Height**</b> (without after treatment unit) in (mm)	29.1 × 21.4 × 31.4 (738 × 544 × 797)
<b>Length × Width × Height***</b> (with after treatment unit) in (mm)	-
<b>Dry Weight</b> lb (kg)	639 (290)

Specifications are subject to change without notice.

Dimensions and dry weight are according to Kubota's standard specification.

Dimensions and weight depend on completed specifications.

\*1: SAE J1349 net stand-by

\*2: SAE J1349 net continuous

\*3: Exclude cooling fan and exclude aftertreatment unit

\*4: Exclude cooling fan and include aftertreatment unit on engine