Specs & Compare

Compare Kubota Engines

Specifications	V3300-E3-BG 30.6 kW / 41.0 HP / 1800 RPM
Emission Regulations	EPA/CARB interim Tier 4 level
Type	Vertical, water cooled 4-cycle diesel engine
Cylinders	4
Bore and Stroke in (mm)	3.86 × 4.331 (98.0 x 110.0)
Displacement cu. in. (L)	202.5 (3.318)
Aspiration	Naturally aspirated
After treatment	-
Stand-by output/speed* kW (HP) / rpm	45.1 (33.6)/ 1800
Continuous output/speed* kW (HP) / rpm	41.0 (30.6)/ 1800

Combustion System	Indirect injection
Fuel System	In-line pump
Length × Width × Height** (without after treatment unit) in (mm)	29.1 × 21.1 × 29.4 (738 × 536 × 746)
Length × Width × Height*** (with after treatment unit) in (mm)	-
Dry Weight lb (kg)	617 (280)

Specifications are subject to change without notice.
Dimensions and dry weight are according to Kubota's standard specification.
Dimensions and weight depend on completed specifications.

*1: SAE J1349 net stand-by
*2: SAE J1349 net continuous
*3: Exclude cooling fan and exclude aftertreatment unit
*4: Exclude cooling fan and include aftertreatment unit on engine